


GROUNDING CONNECTORS



DIMENSIONS



- Color coded GREEN for quick identification as a grounding conductor for copper wire only
- Specifically designed for making positive ground connections and bonding non-metallic sheathed cable

- Live-action square spring draws wires deep into the spring for a safe, tight grip ensuring an excellent connection
- Swept-back wing design enables users to tighten connectors easily by hand.

FOR COPPER WIRE ONLY

CATALOG NO.	UPC CODE	PACKAGING UNIT	WEIGHT	
			CARTON	LBS./CTN.
WWC-GR-H	14142	bag of 25 with header	3,750 (150 bags of 25)	10.55/12.50KG
WWC-GR-C	14127	box of 100	3,200 (32 boxes of 100)	25
WWC-GR-SJ	14250	standard jar of 100	2,000 (20 jars of 100)	19
WWC-GR-J	14149	large jar of 350	4,200 (12 jars of 350)	39
WWC-GR-P	14179	pail of 250	3,000 (12 pails of 250)	25
WWC-GR-B	14128	bag of 500	4,500 (9 bags of 500)	31
WWC-GR-CB	78836	blister box of 25	varies based on quantity ordered	
WWC-GR	14129	bulk	5,500	35
WWC-GR-D	14162	fibre drum	25,000	151

TYPICAL EXAMPLE:

X System grounding wire **Y** System grounding wire **Z** "Through" wire between device and box ground

Note: If "through" wire is a jumper, be sure wire extends below skirt 6" min.

CATALOG NO.	A		B		C		D		E	
	MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	INCH
WWC-GR	8.30	0.327	12.10	0.476	20.20	0.795	9.40	0.370	28.80	1.134

N-TYPE WINGED WIRE CONNECTOR



YELLOW 22-10 AWG


WIRE RANGE: max: 3 #12 min: 4 #22
VOLTAGE: 600 volt max*



RED 22-6 AWG

WIRE RANGE: max: 1 #8 w/3 #12 str. min: 3 #20 • VOLTAGE: 600 volt max*

DIMENSIONS



- Temperature rating 105°C (221°F)
- Made from nylon 6/6 (Polyimide 66)
- Swept-back design provides firm and comfortable twisting
- Inserted with fixed, square-wire spring grabs wires quickly and firmly
- Compact design perfect for tight spaces
- Color coded to industry standards
- Pre-twisting of wires is not necessary
- 1,000 volt maximum in fixtures and signs

FOR COPPER WIRE ONLY

CATALOG NO.	COLOR CODE	UPC CODE	PACKAGING UNIT		WEIGHT	
			CARTON	LBS./CTN.		
WWC-N1-H	yellow	14259	bag of 25 with header	1,000 (40 bags of 25)	5.35	
WWC-N1-C	yellow	14172	box of 100	4,500 (45 boxes of 100)	20	
WWC-N1-CJ	yellow	14234	small jar of 100	5,000 (50 jars of 100)	25	
WWC-N1-SJ	yellow	14248	standard jar of 250	5,000 (20 jars of 250)	24	
WWC-N1-J	yellow	14151	large jar of 600	7,200 (12 jars of 600)	31	
WWC-N1-P	yellow	14257	pail of 450	5,400 (12 pails of 450)	25	
WWC-N1-B	yellow	14252	bag of 500	6,500 (13 bags of 500)	25	
WWC-N1	yellow	14253	bulk	10,000	37	
WWC-N1-D	yellow	14260	fibre drum	45,000	168	
WWC-N2-H	red	14261	bag of 25 with header	1,000 (40 bags of 25)	7.3	
WWC-N2-C	red	14175	box of 100	3,200 (32 boxes of 100)	22	
WWC-N2-SJ	red	14249	standard jar of 100	2,000 (20 jars of 100)	17	
WWC-N2-J	red	14254	large jar of 400	4,800 (12 jars of 400)	32	
WWC-N2-P	red	14258	pail of 250	3,000 (12 pails of 250)	22	
WWC-N2-B	red	14255	bag of 500	4,500 (9 bags of 500)	27	
WWC-N2	red	14256	bulk	10,000	33	
WWC-N2-D	red	14262	fibre drum	25,000	183	

CATALOG NO.	A		B		C		D		E	
	MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	INCH
WWC-N1	7.30	0.287	10.90	0.429	12.50	0.492	10.60	0.417	25.20	0.992
WWC-N2	9.10	0.358	13.20	0.520	14.80	0.583	11.50	0.453	29.50	1.161